

Class A Power Quality Analyser

MI 2893 Power Master XT



The MI 2893 Power Master XT is a hand-held three phase power quality analyzer with a large easy-to-read graphical color display enabling the user to detect harmonics, phasors, waveforms and transients with sampling frequency 1 MSamples/sec in the installation simply by connecting the device. The instrument is designed for a long term recording as well as for troubleshooting power quality problems in three-phase and single-phase power distribution systems. The handy Quick Set buttons makes the instrument more user friendly and are allowing faster data overview for troubleshooting. Advanced PC SW package PowerView3 enables detailed analysis of recorded data, direct and remote reading from the micro SD memory card, analysis of long term records and automatic creation of professional test report.

MEASURING FUNCTIONS

- Voltage: TRMS, peak, crest factor (4-channel);
- Current: TRMS, peak, crest factor (4-channel);
- Power (active, reactive, apparent);
- **Power measurements fully compliant with IEEE 1459 (active, non active, fundamental, harmonic, load un-balance) and classic (vector or arithmetic) method;**
- **VFD (variable frequency drive, 5 Hz – 110 Hz), 400 Hz;**
- Unbalance, flicker measurement;
- Harmonic and interharmonic analysis up to **50th harmonics, THD and TDD measurements;**
- **Energy (active, apparent, reactive, generated, consumed);**
- Capturing and recording of power supply events (shutdowns, interruptions, swells, dips);
- Inrush currents monitoring and recording;
- Waveform/inrush displaying, snapshot and recording;
- **Transients with sampling frequency 1 MSamples/sec;**
- Power quality analysis according to EN 50160, IEEE 519;
- Recording up to 7 adjustable alarms;
- Temperature measurement;
- Power factor, tg fi.

KEY FEATURES

- 4-voltage channels with wide measurement range;
- 4-current channels with support for automatic clamp recognition and "on instrument" range selection;
- Automatic Smart Clamp detection and Smart Clamp range selection;
- Current clamp auto range selection;
- **Sampling frequency on transients recording > 1 MSamples/sec;**
- **Compliance with power quality standard IEC 61000-4-30 Class A;**
- Complete power quality analysis according to EN 50160 including signalling and interharmonics;
- Support for microSD memory card (8-GB supplied with the instrument) up to 32GB;
- Color-coded input terminals and terminal labels to suit your application region;
- Intuitive main menu and large icons that makes the equipment very easy to navigate and configure;
- Powerful PC SW PowerView3 enables downloading, view, analysis of recorded data and professional report creation;
- Flexible clamps (without additional power supply) are included in the Euro set;
- Remote communication via Ethernet (GPS clock synchronization - optional).

APPLICATION

- **High speed transient capturing;**
- Energy consumption optimization;
- Power quality assessment and troubleshooting in low and middle voltage electrical systems;
- Checking power correction equipment performance;
- Long-term analysis;
- Predictive maintenance;
- Verification of electrical system capacity before adding loads.

STANDARDS

Safety

- EN 61010-1

Measurements:

- IEC/EN 61000-4-30, Class A;
- IEC/EN 61557-12;
- IEC/EN 61000-4-7, Class I;
- IEC/EN 61000-4-15;
- EN 50160;
- IEEE 1448;
- IEEE 1459;
- IEEE 519

Electromagnetic compatibility (EMC):

- EN 61326

Váš dodavatel:

MERATEST s.r.o., nám. Em. Zahna 168, Květná, 687 66 Strání

Mob.: +420 721 173 293, Tel.: +421 32 642 0909

e-mail: info@reviznipristroje.cz, web: reviznipristroje.cz

TECHNICAL SPECIFICATION

Voltage inputs	AC+DC
Number of inputs	5
Nominal voltage range	
Three phase connection	Phase (L-N): 50 ... 1000 V RMS Line (L-L): 87 ... 1730 V
Single phase connection	Phase (L-N): 50 ... 500 V RMS
Measuring range	
Three phase connection	10 % ... 150 % of nominal voltage
Single phase connection	10 % ... 110 % of nominal voltage
Max. transient peak voltage	±6 kV
Accuracy	IEC 61000-4-30 Class A, ±0.1% of nominal voltage.
Sampling rate	7 kSamples per second @ 50/60 Hz, synchronization with main frequency 1.7 kSamples per second @ VFD (5 Hz - 110 Hz) 12.2 kSamples per second @ 400 Hz
Mains frequency range	42,5 ... 69,0 Hz ±10 mHz 5 ... 110 Hz ±10 mHz (VFD) 335,0 ... 465,0 Hz ±100 mHz
Current inputs	AC+DC
Number of inputs	4
Measuring range (with A 1227/A 1502 flex clamps)	3 ... 6000 ARMS ±1.5% of m.v.
Measuring range (with A 1281 iron clamps)	50 m ... 1200 ARMS ±0.5% of m.v.
Functions	Measuring range Accuracy
Power (P, Q, S, cos φ, PF...)	Depends on voltage and selected clamps IEC 61557-12 Class 1
Energy	Depends on voltage and selected clamps Active: IEC 62053-21 Class 1 Reactive: IEC 62053-23 Class 2 IEC 61000-4-7 Class 1
Harmonics (DC ... 50th) @50/60 Hz	0 ... 20% of nom. voltage
Harmonics (DC ... 13th) @400 Hz	
Harmonics (DC ... 20th) @VFD (5 - 16 Hz)	
Harmonics (DC ... 13th) @VFD (16 - 33 Hz)	
Harmonics (DC ... 5th) @VFD (33 - 110 Hz)	
Interharmonics (1 ... 50th) @50/60 Hz	0 ... 20% of nom. voltage
Interharmonics (1 ... 20th) @VFD (5 - 16 Hz)	
Interharmonics (1 ... 13th) @VFD (16 - 33 Hz)	
Interharmonics (1 ... 5th) @VFD (33 - 110 Hz)	
Flicker	0.2 ... 10 IEC 61000-4-15 Class F3
Mains signalling	0 ... 15% of nom. voltage IEC 61000-4-30 Class A
Unbalance	Voltage: 0 ... 5% Current: 0 ... 20%
Temperature	-10 ... 85 °C ±0.5 °C
Dips, Swell	10 ... 150% of nom. voltage ±0.2 % of nominal voltage
Interrupts	0 ÷ 10% of nom. voltage ±1 cycle
Recorders	
Memory	8GB microSD, up to 32GB supported
General recorder	
Integration period	1s ... 2h
Recorded signals	> 1000 (voltages, currents, harmonics, power...) Minimal, maximal, average and average ON value per interval, including - Voltage events (dip, swell, interrupt) - Custom alarms (up to 7 programmable alarms) - Signalling (up to two selectable frequencies) - Transients - Inrush
Duration	> 1 year (depends on size of SD card at 10 min registration period)
Waveform recorder	
Duration	Up to 60 seconds duration and 30 seconds pretrigger of voltage and current waveform Up to 1500 records
Trigger	Manual, Voltage Events, Custom Alarms, Voltage or current level (inrush), Time interval
Transient recorder	
Sampling rate	1 MSamples/sec; simultaneously on all 8 channels
Duration	Up to 5 cycles of voltage and current waveforms
Trigger	Transient selection measurement between L-N/L-GND Envelope and level trigger simultaneously Transient recorder runs simultaneously with general and waveform recorder Set & go transient setup; predefined setup (low and high level) for current and voltage trigger
General	
Display	4.3 inch color TFT (480 x 272)
Communication	USB, Ethernet
Time synchronisation	GPS receiver (A.1355)
Power supply	With power supply adapter or 6 x NiMH rechargeable batteries, size AA
Overvoltage category	CAT IV / 600 V For three phase connection CAT III 1000 V
Weight	1.1 kg
Dimensions	230 x 140 x 80 mm

ORDERING INFORMATION



MI 2893 Advanced set (AD)

- Instrument Power Master XT
- 1-phase flexible current clamps 3000 / 300 / 30 A (A 1502), 4 pcs
- Test probe, (brown, black, grey, green, blue), 5 pcs
- Crocodile clip, (brown, black, grey, green, blue), 5 pcs
- Voltage measurement lead, (brown, black, grey, green, blue), 5 pcs
- Labels for colour coding
- Temperature probe
- microSD memory card 8.0GB
- microSD card reader
- PC SW PowerView3
- RS232, USB and Ethernet patch cable
- Power supply adapter
- 1.2 V NiMH rechargeable battery, 6 pcs
- Professional protective waterproof case (A 1685)
- Instruction manual
- Calibration certificate

MI 2893 Euro set (EU)

- With 1-phase flexible current clamps 3000 / 300 / 30 A (A 1227), 4pcs

MI 2893 Standard set (ST)

- Without flexible current clamps

OPTIONAL ACCESSORIES

Photo	Order No.	Acc. description
	A 1501	1-phase current clamp
	A 1502	1-phase current clamp
	A 1503	1-phase current clamp
	A 1445	1-phase current clamp
	A 1446	1-phase current clamp
	A 1033	Current clamp 1000 A / 1 V
	A 1281	Current clamp 1000/100/5 A / 1 V
	A 1037	Current transformer 5 A / 1 V
	A 1561	Connection cable for current clamp (A 1069)
	A 1069	Mini current clamp 100 A / 1 V
	A 1588	Current clamp 0.5/5/50 A
	A 1636	Current clamp DC 2000 A/AC 1000 A
	A 1355	GPS reciver
	S 2014	Safety fuse adapter, 3 pcs
	S 2015	Safety flat clamp, 4 pcs
	A 1391 PQA	AC/DC Current clamp 300/40 A / 1 V
	A 1622	WiFi / 3G modem

Váš dodavatel:

MERATEST s.r.o., nám. Em. Zahna 168, Květná, 687 66 Strání

Mob.: +420 721 173 293, Tel.: +421 32 642 0909

e-mail: info@reviznipristroje.cz, web: reviznipristroje.cz



METREL®